### (19) World Intellectual Property Organization

International Bureau



# I TORRE BINGER IN REPURBUSH COM REPUBLICATION IN AN EXCHANGE COM BERN COME AND A COMPANION FOR THE COMPANION

(43) International Publication Date 3 March 2005 (03.03.2005)

**PCT** 

# (10) International Publication Number WO 2005/020449 A2

(51) International Patent Classification7:

H04B 1/06

(21) International Application Number:

PCT/GB2004/003566

(22) International Filing Date: 19 August 2004 (19.08.2004)

(25) Filing Language:

**English** 

(26) Publication Language:

English

(30) Priority Data:

0319518.7

19 August 2003 (19.08.2003) GI

(71) Applicant (for all designated States except US): PLEX-TEK LIMITED [GB/GB]; London Road, Great Chesterford, Essex CB10 1NY (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): RICHARDS, Tony [GB/GB]; Plextex Limited, London Road, Great Chesterford, Essex CB10 1NY (GB). FITZ, Steve [GB/GB]; 16 New Road, Great Baddow, Chelmsford, Essex CM2 7QT (GB).

- (74) Agents: MCCANN, Heather et al.; Electronic Intellectual Property, Suite 308, The Foundry, 156 Blackfriars Road, London SE1 8EN (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PROXIMITY DETECTING APPARATUS



(57) Abstract: Embodiments of the invention are concerned with proximity detecting apparatus and are concerned particularly with radio frequency proximity detecting apparatus that operate in the low radio frequency range. Embodiments of the present invention also relate to radio frequency transmitter and radio frequency receiver designs generally. Arrangements according to the invention embody a radio frequency receiver for use in a proximity detecting system, the radio frequency receiver comprising at least one antenna coil operable to receive radio frequency signals; tunable receiver circuitry arranged in operative association with the antenna coil and being arranged to modify the frequency at which radio signals are received by the radio frequency receiver; and a signal processor arranged to amplify and filter signals received by the radio frequency receiver; wherein the radio frequency receiver is operable to receive and process radio signals of frequencies between 100kHz and 10MHz. By operating in the low frequency range, multi-path problems associated with high frequency equipment (such as reflections from objects located between the path of the transmitter and receiver) are significantly reduced, whilst distance between transmitter and receiver can be identified extremely accurately.





## WO 2005/020449 A2



#### Published:

 without international search report and to be republished upon receipt of that report For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.